

Spannungseinsatzbereich, Baureihe ILI
Range of operating voltage, type ILI
Intervalle de mises sous tension, version ILI
Rango de ajuste de tensión, variante de serie ILI
Campo di applicazione della tensione, serie ILI

Drehstrommotor, vierpolig 3~230V/400V
 Three phase alternating current motor, quadripolar 3~230V/400V
 Moteur à courant triphasé, quadripolaire 3~230V/400V
 Motor trifásico, cuatro polos 3~230V/400V
 Motore a corrente trifase, a quattro poli 3~230V/400V

Betriebsart Mode Couplage Modo de funcionamiento Modalità operativa	Bg Frame size HA Tamaño mod.	Lüfterdurchmesser Blower diameter Diamètre des ventilateurs Diámetro del ventilatore Diametro del ventilatore	Spannungsbereich Range of voltage Plage de tension Rango de tensiones Campo di tensione		Max. zulässiger Strom Max. permissible current Courant max. admissible Corrente máxima permitida Corrente massima consentita	max. Leistungsaufnahme max. power input max. puissance absorbée Consumo máxima de energía Potenza massima assorbita		
			50Hz (V)	60Hz			50Hz (A)	60Hz
1~ Δ	90	169	230-277	230-277	0.18	0.16	40	37
	100	187	230-277	230-277	0.18	0.16	40	37
	112	210	230-277	230-277	0.18	0.16	40	38
	132	250	230-277	230-277	0.34	0.25	58	55
	160-200	300	230-277	230-277	0.34	0.28	63	68
3~ Y	90	169	346-525	380-575	0.12	0.11	58	54
	100	187	346-525	380-575	0.11	0.11	57	54
	112	210	346-525	380-575	0.11	0.11	57	55
	132	250	346-525	380-575	0.25	0.22	71	63
	160-200	300	346-525	380-575	0.25	0.22	80	83
	204-249	375	346-525	380-575	0.31	0.34	154	223
			346-690 *	380-690	0.53	0.36	238	247
	250-450	470	346-525	380-575	0.44	0.72	281	451
			346-690 *	380-690	0.84	0.72	360	478
	355-560	684	346-525	380-575	1.76	2.65	969	1600
346-690 *			380-690	2.00	2.60	1101	1629	
3~ Δ	90	169	200-303	220-332	0.20	0.19	58	54
	100	187	200-303	220-332	0.20	0.19	57	54
	112	210	200-303	220-332	0.20	0.19	57	55
	132	250	200-303	220-332	0.44	0.38	71	63
	160-200	300	200-303	220-332	0.43	0.37	80	83
	204-249	375	200-400	220-400	0.91	0.62	238	247
			200-400 *	220-400	0.91	0.62	238	247
	250-450	470	200-400	220-400	1.45	1.25	360	478
			200-400 *	220-400	1.45	1.25	360	478
	355-560	684	200-400	220-400	3.50	4.50	1101	1629
200-400 *			220-400	3.50	4.50	1101	1629	

*Variante bis 690V ohne UL-Zulassung

*Version up to 690V without UL-certification

Hinweis: Bg204 > ohne Stufenrohr mit Lüfter 375mm
 Bg249 > wie Bg250 jedoch noch mit Lüfter 375mm

mit b-seitigem Referenzlagerschild / with bearing shield of reference on side b / avec de référence flasque latérale b / placa de referencia en el lado b / con targhetta cuscinetti di riferimento lato b