



1100	1124	1181	1214	16	40	9850
1000	995	1057	1075	13	36	7600
900	894	955	974	13	32	6000
800	797	854	877	13	28	4800
750	762	817	842	13	28	4400
700	696	752	776	13	28	3650
600	596	646	676	13	20	2650
500	494	544	574	13	20	1820
450	465	515	545	13	16	1600
400	393	443	473	13	16	1213
350	342	387	422	11	12	830
300	310	355	390	11	12	680
250	261	296	341	9	8	480
200	208	243	268	9	8	300
DN	Inside diameter (mm) d ₁	Bolt circle (mm) k	External diameter (mm) D	Bore (mm) d ₂	Qty.	Vent area (cm ²)

For installation between DIN 2632 welding neck flange dimensions are the same but no holes in the flange portion

7	1	Bolt M10 ISO 4017			
6	2	Washer M10 ISO 7091			
5	1	Nut M10 ISO 4032			
4	1	Process Flange			
3	1	Flange Gasket integrated			
2	1	Explosion Vent			
1	1	Counter Flange	1	22.09.15	Marczyk
Pos.	Qty.	Description	Rev.	Date	Name

Scale: -- | Tolerances: ISO 2768 - mL

BRILEX Explosion Vent

Drawing: Round Vents

Flange dimensions: DN 200 - 1100

Vent size: DN 200 - 1100

en 1/1

Rev. 1 A4